



mastabase

bedding cement

mastabase is a plaster based cement for bedding tape into recessed edges and butt joints. It is also suitable for second coating plasterboard joints, internal and external angles and fastener heads. **mastabase** has a consistent working time of 45 minutes with a 60 minute setting time.

All Siniat jointing and finishing compounds can be used over **mastabase** as a final coat.

performance

Mixing

Wets out quickly and mixes easily by hand or electric mixer for a smooth, creamy consistency.

Trowelling

Easy to trowel for both hand and mechanical tools and has good body on the trowel and on the hawk.

Setting Time

Shorter working time is ideal for smaller jobs.

Drying

Quick drying means less waiting before sanding, with time available for fine edges when feathering. **mastabase** has good resistance to cracking in internal angles.

Strength

A hard setting cement providing the strongest joint when used with paper tape and yet easily scraped back between coats.

Sustainable

Low VOC meeting sustainable building project requirements.

key benefits

- high joint strength
- easy to scrape back
- quick drying



product information

product size	20kg and 10kg paper bag
type	Plaster based bedding cement
mixing ratio	1L of water to 2kg of mastabase
working time	45 - 60 minutes
setting time	60 minutes
system usage	✓ Bedding ✓ Second coat ✓ Standard ✓ Fire rated ✓ Wet area systems
voc	<50g/L

application

- **mastabase** is suitable for dry and wet areas and where a fire resistance level is specified.
- Must not be applied over air drying compounds.
- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container.
- Add the powder into water, mixing continuously to a smooth, creamy consistency.
- Only mix enough cement to be used in 45 minutes and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.
- Siniat strongly recommends the use of paper tape for jointing.
- Where fibreglass tape is used, the joint must be back blocked with **mastablock**. Fibreglass tape must not be used in fire rated and wet area applications.
- Allow **mastabase** to set completely between coats.

optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring **mastabase** does not dry out before setting has taken place under severe hot dry conditions.



Quality
ISO 9001



All Siniat products have been developed to meet the specific needs of the Australian market. Products manufactured in Australia comply with quality systems certified as complying with AS/NZS ISO 9001:2008 and meet the requirements of AS/NZS 2588, Gypsum Plasterboard.



The following Siniat products have been independently certified by Global GreenTag to GreenRate Level A: **mastashield**, **fireshield**, **fireshield h**, **soundshield**, **watershield**, **spanshield**, **multishield**, **curveshield**, **opal**, **trurock** and **trurock hd**. Compliance certificates are available on siniat.com.au.



All Siniat plasterboard and metal products are available on the Siniat Carbon Neutral Opt-In program to help you meet your sustainability goals. Visit siniat.com.au to find out more.

Disclaimer

Products manufactured and systems designed by Etex Australia Pty Ltd and branded Siniat, are produced in accordance with the Building Code of Australia and relevant Australian Standards. Information in this document is to be used as a guide only and is subject to project approval as many aspects of construction are not comprehensively covered. It is also the responsibility of the project to determine if Siniat's products and systems are suitable for the intended application. Etex Australia Pty Ltd will not be held responsible for any claims resulting from the installation of its products or other associated products not in accordance with the recommendations of the manufacturer's technical literature or relevant Australian Standards. Siniat technical information is regularly updated. To ensure this document is current with the latest information, visit siniat.solutions

Siniat.solutions provides a host of online solutions for your product

siniat SELECT[®]

offers an online system selector and custom design specification proposal, developed by us and catered to your project's requirements.

siniat CALCULATE[®]

is a range of online calculation tools for the professional. Explore siniat.solutions on siniat.com.au.



Etex Australia Pty Ltd

ABN 61 003 621 010
31 Military Road, Matraville
NSW 2036

siniat.com.au



warranty

Siniat's products are guaranteed by a 10 Year Warranty. For details visit siniat.com.au

technical advice
AU 1300 724 505