



## key benefits

- high joint strength
- easy to scrape back
- longer working time

# mastalongset

## bedding cement

**mastalongset** is a plaster based cement for bedding tape into recessed edges and butt joints. It is also suitable for second coating plasterboard joints, internal and external angles and fastener heads. **mastalongset** has an extended working time of 65 minutes, making it particularly suitable for mechanical tools and ideally suited to larger jobs.

All Siniat jointing and finishing compounds can be used over **mastalongset** as a final coat.

## performance

### Mixing

Mixes to a smooth, creamy consistency by hand or electric mixer.

### Trowelling

Very easy to trowel for both hand and mechanical tools, and has great body on the trowel and on the hawk.

### Setting Time

Longer working time reduces frequency of mixes, resulting in more metres covered and less wastage.

### Drying

Plenty of time to obtain good thin edges when feathering and re-trowelling as it does not dry out too fast.

### Strength

A hard setting cement providing the strongest joint when used with paper tape.

### Sustainable

Low VOC meeting sustainable building project requirements.



## product information

<b>product size</b>	20kg paper bag
<b>type</b>	Plaster based bedding cement
<b>mixing ratio</b>	1L of water to 2kg of <b>mastalongset</b>
<b>working time</b>	65 minutes
<b>setting time</b>	80 minutes
<b>system usage</b>	✓Bedding ✓Second coat ✓Standard ✓Fire rated ✓Wet area systems
<b>voc</b>	<50g/L

## application

- **mastalongset** is suitable for first and second coating on all internal lining applications, including fire rated and wet areas.
- Must not be applied over air drying compounds.
- Always use clean tools and containers.
- Pour the required amount of clean tap water into a container. Add the powder into water, mixing continuously to a smooth, creamy consistency.
- Only mix enough cement to be used in 65 minutes, and do not contaminate with previously mixed batches. Once the material starts to set it cannot be remixed.
- Siniat strongly recommends the use of paper tape for jointing.
- Where fibreglass tape is used, the joint must be back-blocked with **mastablock**. Fibreglass tape must not be used in fire rated and wet area applications.
- Allow **mastalongset** to set completely between coats.

## optimise product performance by:

- Storing in a dry, well ventilated environment fully protected from the weather.
- Washing tools before product dries and hardens.
- Ensuring **mastalongset** does not dry out before setting has taken place under severe hot dry conditions.



Quality  
ISO 9001



All Siniat products have been developed to meet the specific needs of the Australian market. Products manufactured in Australia comply with quality systems certified as complying with AS/NZS ISO 9001:2008 and meet the requirements of AS/NZS 2588, Gypsum Plasterboard.



The following Siniat products have been independently certified by Global GreenTag to GreenRate Level A: **mastashield**, **fireshield**, **fireshield h**, **soundshield**, **watershield**, **spanshield**, **multishield**, **curveshield**, **opal**, **trurock** and **trurock hd**. Compliance certificates are available on [siniat.com.au](http://siniat.com.au).



All Siniat plasterboard and metal products are available on the Siniat Carbon Neutral Opt-In program to help you meet your sustainability goals. Visit [siniat.com.au](http://siniat.com.au) to find out more.

#### Disclaimer

Products manufactured and systems designed by Etex Australia Pty Ltd and branded Siniat, are produced in accordance with the Building Code of Australia and relevant Australian Standards. Information in this document is to be used as a guide only and is subject to project approval as many aspects of construction are not comprehensively covered. It is also the responsibility of the project to determine if Siniat's products and systems are suitable for the intended application. Etex Australia Pty Ltd will not be held responsible for any claims resulting from the installation of its products or other associated products not in accordance with the recommendations of the manufacturer's technical literature or relevant Australian Standards. Siniat technical information is regularly updated. To ensure this document is current with the latest information, visit [siniat.solutions](http://siniat.solutions)

#### Siniat.solutions provides a host of online solutions for your product

#### **siniat SELECT**<sup>®</sup>

offers an online system selector and custom design specification proposal, developed by us and catered to your project's requirements.

#### **siniat CALCULATE**<sup>®</sup>

is a range of online calculation tools for the professional. Explore [siniat.solutions](http://siniat.solutions) on [siniat.com.au](http://siniat.com.au).



**Etex Australia Pty Ltd**

ABN 61 003 621 010  
31 Military Road, Matraville  
NSW 2036

[siniat.com.au](http://siniat.com.au)



#### warranty

Siniat's products are guaranteed by a 10 Year Warranty. For details visit [siniat.com.au](http://siniat.com.au)

technical advice  
**AU 1300 724 505**